REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

1. REPORT DATE *(DD-MM-YYYY)*	2. REPORT TYPE	3. DATES COVERED *(From - To)*
09-01-2005	Final Report	01/23/03 - 09/30/04

4. TITLE AND SUBTITLE

Bayesian Inversion of Radar Clutter

5a. CONTRACT NUMBER

5b. GRANT NUMBER

N00014-03-1-0393

5c. PROGRAM ELEMENT NUMBER

6. AUTHOR(S)

Gerstoft, Peter, Hodgkiss, William, Kuperman, William A.

5d. PROJECT NUMBER

5e. TASK NUMBER

5f. WORK UNIT NUMBER

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

Marine Physical Laboratory
Scripps Institution of Oceanography
291 Rosecrans Street
San Diego, CA 92106

8. PERFORMING ORGANIZATION REPORT NUMBER

MPL TM-487

9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)

Office of Naval Research
Ballston Centre Tower One
800 N. Quincy Street
Arlington, VA 22217
Dr. Ronald Ferek. 322MM

10. SPONSOR/MONITOR'S ACRONYM(S)

ONR

11. SPONSOR/MONITOR'S REPORT NUMBER(S)

12. DISTRIBUTION/AVAILABILITY STATEMENT

13. SUPPLEMENTARY NOTES

14. ABSTRACT

This report describes the research performed on behalf of the Office of Naval Research (grant #N00014-03-1-0393) to estimation of refractivity profiles from radar clutter returned. Through simulation and experimental results it is shown that the radar clutter return can be used for extracting refractivity profiles. Of particular interest is the uncertainty in these estimates and it is demonstrated how these parameters can be used for radar performance prediction.

15. SUBJECT TERMS

Bayesian inversion, radar, clutter, refractivity profiles

16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT	b. ABSTRACT	c. THIS PAGE	None	8	Erika Wilson
unclassified	unclassified	unclassified			19b. TELEPHONE NUMBER *(Include area code)* 858-534-1802

Standard Form 298 (Rev. 8/98)
Prescribed by ANSI Std. Z39.18

Bayesian Inversion of Radar Clutter

Peter Gerstoft
William S. Hodgkiss
William A. Kuperman

Marine Physical Laboratory
Scripps Institution of Oceanography
291 Rosecrans Street
San Diego, CA   92106

Bayesian Inversion of Radar Clutter

Final Report

For the period 21 January 2003 - 30 September 2004

Peter Gerstoft
Marine Physical Laboratory, Scripps Institution of Oceanography
La Jolla, CA 92093-0238
phone: (858) 534-7768   fax: (858) 534-7641   email: gerstoft@ucsd.edu

William S Hodgkiss
Marine Physical Laboratory, Scripps Institution of Oceanography
La Jolla, CA 92093-0238I
phone: (858) 534-1798   fax: (858) 534-7641   email: wsh@mpl.ucsd.edu

William A Kuperman
Marine Physical Laboratory, Scripps Institution of Oceanography
La Jolla, CA 92093-0238
phone: (858) 534-7990   fax: (858) 534-7641   email: wak@mpl.ucsd.edu

Abstract

Estimation of refractivity profiles from radar clutter return is discussed. Through simulation and experimental results it is shown that the radar clutter return can be used for extracting refractivity profiles. Of particular interest is the uncertainty in these estimates and it is demonstrated how these parameters can be used for radar performance prediction.

Research Summary

The goal of this project was to develop inversion approaches that enable the estimation of refractivity profiles and the associated uncertainty. Further to develop methods for mapping the refractivity parameters and their associated uncertainty into propagation.

The results of this reseach are documented in five refered jornal papers [1-6] and one conference proceeding [7].

Our inversion approach has mainly been based on SAGA and focused on estimation of the parameters corresponding to the field that gives the best fit to the data. We have concentrated on demonstrating the feasibility of RFC using an efficient 11-parameter description of the environment. The quality of the inversion was addressed by comparing the field using the estimated parameters to a measured field [1-6]. Little has been done to indicate the quality of the solution for each parameter, either with the variance of parameter-estimate or preferably the complete *a posteriori* distribution. We have already done much work on this in an ocean acoustic context [Gerstoft 98], but this has not been explored in

our RFC processing to date. This entails developing likelihood formulations and importance sampling algorithms. This inversion approach shows the information content in the data, the importance of each parameter, and the quality of the inversions [1-2].

The simulated data are generated based on the helicopter measured range-dependent refractivity profiles (Run 7) for the Wallops 98 experiment [Gerstoft03a], see Fig 1. A range interval from 10-100 km is used. A simple trilinear model (Fig 2) is used for the inversion of the refractivity profile as outlined in the Appendix of [Gerstoft03a]. We then search for tri-linear refractivity parameters at 0 and 100 km range. To obtain refractivity profiles at other ranges the parameters are interpolated linearly. The first 3 parameters were given a uniform distribution but the slope was given a non-uniform distribution as indicated in Fig 3 (left bottom). This is because a negative mixed layer slope is only likely for shallow ducts (low base height).

First, 90,000 environmental models are selected from the prior distributions, Fig 3 left. Using these environmental models, 90,000 vectors of propagation loss versus range are precomputed. The posteriori distribution (right column Fig. 3) is computed as a product of the prior distributions with the likelihood distribution. The likelihood distribution shows how well the environmental models describe the data. We note that the overall behavior of the posteriori distributions seems reasonable.


*Figure 1 (a) The observed refractivity profile and (b) the simulated propagation loss data.*

Figure 2 Trilinear model. We invert for the base height, thickness, M-deficit and the mixed layer slope.

Figure 3 Prior (left) and posteriori (right) distributions of the parameter estimates. The abscissa "1" (lower panel) and "2"(upper panel) refers to the values at emitter and receiver, respectively.

The overall objective is to estimate posteriori statistics of propagation loss. An example of this is shown in Fig 4. We compute the average priori propagation loss based on an even weighting of the propagation loss from each generated refractivity model. The posteriori probability distribution of the propagation loss is based on weighting the propagation loss from each refractivity model with the posteriori probability.

The average prior and posteriori propagation losses are shown in Fig. 4b and c. It is seen that the average posteriori propagation loss identifies a ducting environment as observed in the data, Fig. 4a, but the prior does not.

The probability distribution of the propagation loss then is computed at all ranges and depths. Both prior (Fig. 5 left) and posteriori (Fig. 5 right) propagation loss are shown at 10 and 100 m height as a function of range. Clearly, the posteriori plot shows how the data has improved our estimation of propagation loss.

Figure 4: (a) The propagation-loss field from the true environment (from Fig. 1a) and the average propagation-loss field based on (b) prior information, and (c) posteriori information (bottom).


Figure 5 Prior (left) and posteriori (right) propagation loss probability distributions at 10 m (top) and 100 m (bottom).

REFERENCES

[1] C. Yardim, P. Gerstoft, and W.S. Hodgkiss, Estimation of radio refractivity from radar clutter using Bayesian Monte Carlo analysis, submitted IEEE J Antenna and Propagation (2005).

[2] L.T. Rogers, M. Jablecki, and P Gerstoft, Posterior distribution of a statistic of propagation loss estimated from radar sea data in press Radar Science, 2005.

[3] P. Gerstoft, W.S. Hodgkiss L. T. Rogers and M. Jablecki, Probability distribution of low altitude propagation loss from radar sea-clutter data, Radio Science, 39, doi:10.1029/2004/RS003077, Nov. 2004

[4] D.J. Battle, P. Gerstoft, W.S. Hodgkiss, W.A. Kuperman, and P.L. Nielsen, "Bayesian model selection applied to self-noise geoacoustic inversion," J. Acoust. Soc. Am. 16, pp 2043-2056, 2004.

[5] P. Gerstoft, L.Ted Rogers, and W.S. Hodgkiss, J. Krolik, Inversion for refractivity parameters from radar sea clutter, Radio Science, Vol 38, paper 18, pp 1-22, March 2003.

[6] P. Gerstoft, L. Ted Rogers, W.S. Hodgkiss and L. J Wagner, Refractivity estimation using multiple elevation angles, IEEE J.. Oceanic Engineering, 28 (3), 513-525, 2003.

[7] P. Gerstoft, L.Ted Rogers, and W.S. Hodgkiss, Posterior estimation of low attitude propagation loss from radar sea clutter data, IEEE J. Oceans conference, San Diego (2003).